

Foot ascender to improve rope ascending in a rope access. Used in conjunction with LIFT and CAM CLEAN.

DESCRIPTION

Durable construction with stainless cast steel.

Fully adjustable webbing to achieve the best comfort of use.

Marked with unique production number.

Available in left and right version.

Lower part is reinforced with tubular webbing for longer use.



Quick and easy to adjust with Oring.

Stainless steel toothed cam for higher corrosion resistance and for any conditions (frozen or dirty ropes).

Cam/lever mechanism fully integrated into the body.

For use with \emptyset 8–13 mm ropes, static and dynamic.

KEY FEATURES

unique number

quick and easy to adjust

STANDARDS

FOOT LIFT is not a PPE

FEATURES



120 kg



Ø 8–13 mm 160 g



160 g / 5.6 oz



unique number




warranty

MATERIALS

TECHNICAL DATA



- 50 % steel
- **30** % light alloy
- 20 % PA







for Ø 8–13 mm ropes



MAINTENANCE

Lifetime of this product is not strictly limited by the manufacturer. Depending on the condition of the product and its history it may be necessary to retire it immediately (e.g. visible signs of damage). Lifetime of this product can be influenced by various factors such as: frequent or improper use; usage environment (humidity, freezing, ice); wear; corrosion; serious stress with relative deformation; exposure to heat sources; improper storage; etc.











read instructions

beware of salt

washing

drying

silicon oil

OTHER VIEWS





left



right

NOTES



