

EXPERT

3D SPEED

Fully adjustable harness for rope access with a padded wide waist belt, leg loops and shoulder straps. Shoulder straps can be totally removed and the harness can be used as a sit harness only. Suitable also for work positioning, fall arrest and work restraint situations.

DESCRIPTION

Shoulder attachment points for confined space rescue.

Name tag at a clearly visible place.

Highlighted marking of connection points according to EN 361.

OXY triple lock carabiner used for the connection of the shoulder part to the main point to increase the space for chest ascender attachment.



All steel components finished with E - coating for higher corrosion resistance.

Ergonomic braided gear loops with a bearing capacity of 15 kg.

SPEED buckles enable fluent and fast adjustment to fit a user's body.

Additional loops on the leg loops and waist belt with a bearing capacity of 5 kg for better gear orientation.

Anatomic leg loops are covered with a strong PES fabric providing high abrasion resistance.



Reflective straps on the shoulders for higher visibility.

Wide elastic band at left shoulder strap for the gear attachment (e.g. transmitter).

Chest ascender smart fixation system with a plastic cover on the OXY carabiner increasing the durability of the webbing.

Super comfortable wide waist belt padding provides maximum comfort when working at heights.

Reflective straps and printing on the waist belt increase the visibility in dark working conditions.

KEY FEATURES

- shoulder straps can be totally removed and the harness can be used as a sit harness only
- chest ascender smart fixation system

STANDARDS

CE 1019

EN 361 EN 358
EN 813 EN 1497

FEATURES



M/L = 2 415 g
85.2 oz



150 kg




unique number




warranty

MATERIALS




- 26 % stainless steel
- 25 % PES
- 17 % aluminum alloy
- 13% PAD
- 13 % EVA foam
- 6 % polyethylene

TECHNICAL DATA




SIZE	S	M/L	XL
A [cm/in]	65-80 / 25-31	75-100 / 29-39	85-130 / 33-51
B [cm/in]	45-60 / 18-24	50-75 / 20-29	50-75 / 20-29
C [cm/ft]	150-170 / 4.92-5.57	160-180 / 5.25-5.9	175-205 / 5.74-6.73

OTHER VIEWS




3/4 view

Front and back attachment points for descender placement or work positioning according to EN 813, EN 358.




back view

Strength webbing on the waist belt is stitched in the way that at normal working situation the body weight is absorbed by the padding only. Heavier items up to 35 kg can be attached here.




park position

2 side attachment points for work positioning according to EN 358.



work position



PORTER/PORTER XL

Slots at the waist belt for PORTER and PORTER XL tool holder to carry your tools and gear.

COMPARISON
EXPERT 3D - EXPERT III

- fall arrest indicator, lanyard parking attachment element, improved ergonomic waist belt, wide comfortable waist belt
- wide anatomic padded leg loops
- colorfully highlighted 4 gear loops, ergonomic braided front gear loops, accessory loops on the waist belt and leg loops
- special slot on the waist belt for better fixation of the PORTER/PORTER XL carabiner
- leg loops are covered with a polyester fabric for higher abrasion resistance
- reflective straps on the waist belt and shoulder straps increase the visibility of the harness
- on the waist belt and shoulders a vertically stitched webbing creates the holes for fixing the equipment
- wide rubber band on the shoulder for the fixation of devices (e.g. cell phone)



EXPERT III

MAINTENANCE


Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use. However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.



beware of UV



beware of chemicals



beware of salt



washing








drying



read instructions

EXPERT 3D SPEED STEEL AND RELATED PRODUCTS

									
EXPERT 3D SPEED		EXPERT 3D SPEED black		EXPERT 3D SPEED STEEL		EXPERT 3D STANDARD		EXPERT 3D STANDARD black	
SIZE	CODE	SIZE	CODE	SIZE	CODE	SIZE	CODE	SIZE	CODE
S	W0079DR02	S	W0079DB02	S	W0080DR02	S	W0078DR02	S	W0078DB02
M/L	W0079DR03	M/L	W0079DB03	M/L	W0080DR03	M/L	W0078DR03	M/L	W0078DB03
XL	W0079DR05	XL	W0079DB05	XL	W0080DR05	XL	W0078DR05	XL	W0078DB05